



PURITY



PURE HYDROGEN GENERATOR

for heat treatments and biomethanation
per trattamenti termici e biometanazione



ITALIAN TECHNOLOGY

- Absolute Purity of the Gas
Purezza assoluta del Gas
- Easy to use
Facile da usare
- Low Consumption
Basso consumo
- Plug & Play System
Sistema Plug & Play
- No maintenance
Nessuna manutenzione
- One unit, no auxiliaries
Una unità, niente ausiliari





PURE HYDROGEN GENERATOR



MODELS AVAILABLE

The new Sirio on-site hydrogen generator, thanks to the very high levels of purity guaranteed by the ErreDue's PEM (Proton Exchange Membrane) technology, perfectly meets the needs of those applications where a moderate amount of pure and compressed gas is required, such as metal heat treatment and Biomethane production processes.

Sirio is Plug & Play: thanks to its simplicity of use and its autonomy, it is sufficient to connect it to an electrical power source and fill the tank with water to immediately produce pure hydrogen at the necessary pressure and flow rate. In fact, it does not require any auxiliary system: the unit includes a generator, the water tank and a purification system for the produced gas.

The hydrogen flow rate starts from 0.5 m³/h up to 2 m³/h, it's also possible to connect several systems in parallel. The maximum pressure generated reaches 15 bar in the standard models and is customizable up to 30 bar on request.

Sirio ErreDue hydrogen generators can be monitored and managed remotely thanks to the integrated connectivity and ErreDue's remote assistance service.

	SIRIO 50	SIRIO 75	SIRIO 100	SIRIO 125	SIRIO 150	SIRIO 175	SIRIO 200
GAS FLOW RATE	0.5 (Nm ³ /h)	0.75 (Nm ³ /h)	1 (Nm ³ /h)	1.25 (Nm ³ /h)	1.5 (Nm ³ /h)	1.75 (Nm ³ /h)	2 (Nm ³ /h)
GAS PURITY "N" VERSION				99.99%			
GAS PURITY "D" VERSION				99.999%			
GAS DEW POINT "N" VERSION				≤-15°C			
GAS DEW POINT "D" VERSION				≤-50°C			
WORK PRESSURE			15 bar (optional 30 bar)				
AVERAGE ELECTRIC CONSUMPTION				4.8kW/m ³			
POWER SUPPLY			3x400Vac+N - 50/60Hz				
WATER CONSUMPTION AT MAXIMUM POWER	0.4 L/h	0.6 L/h	0.8 L/h	1 L/h	1.2 L/h	1.4 L/h	1.6 L/h
DIMENSIONS (L X W X H)				700 x 830 x 1700 (mm)			
GAS CONNECTION				¼" gas			
NETWORK CONNECTION				Ethernet - Modbus TCP/IP			
WEIGHT	300 Kg	305 Kg	310 Kg	340 Kg	345 Kg	350 Kg	355 Kg

MODELLI DISPONIBILI

Il nuovo generatore di idrogeno on site Sirio, in virtù degli altissimi livelli di purezza garantiti dalla tecnologia PEM (membrana a scambio protonico) ErreDue, risponde perfettamente alle esigenze di tutte quelle applicazioni dove si renda necessaria una moderata quantità di gas puro e compresso, come ad esempio il trattamento termico dei metalli e i processi di produzione di Biometano.

Sirio è Plug & Play: grazie alla sua semplicità di utilizzo e alla sua autonomia è sufficiente collegarlo ad una fonte di alimentazione elettrica e riempire di acqua il serbatoio per poter produrre da subito idrogeno purissimo alla pressione e alla portata necessarie. Non necessita, infatti, di sistemi ausiliari: nell'unità sono compresi generatore, serbatoio acqua e sistema di purificazione del gas prodotto.

La portata di idrogeno parte dagli 0,5 m³/h fino ad arrivare ai 2 m³/h, è possibile anche collegare più sistemi in parallelo. La pressione massima generata arriva fino ai 15 bar nei modelli a catalogo ed è personalizzabile fino a 30 bar su richiesta.

I generatori di idrogeno Sirio ErreDue possono essere monitorati e gestiti a distanza grazie alla connettività integrata e al servizio di assistenza remota ErreDue.

	SIRIO 50	SIRIO 75	SIRIO 100	SIRIO 125	SIRIO 150	SIRIO 175	SIRIO 200
PORTATA GAS	0.5 (Nm ³ /h)	0.75 (Nm ³ /h)	1 (Nm ³ /h)	1.25 (Nm ³ /h)	1.5 (Nm ³ /h)	1.75 (Nm ³ /h)	2 (Nm ³ /h)
PUREZZA GAS VERSIONE "N"				99.99%			
PUREZZA GAS VERSIONE "D"				99.999%			
GAS DEW POINT VERSIONE "N"				≤-15°C			
GAS DEW POINT VERSIONE "D"				≤-50°C			
PRESSIONE DI LAVORO			15 bar (opzionali 30 bar)				
CONSUMO ELETTRICO MEDIO				4.8kW/m ³			
ALIMENTAZIONE ELETTRICA			3x400Vac+N - 50/60Hz				
CONSUMO ACQUA ALLA MASSIMA POTENZA	0.4 L/h	0.6 L/h	0.8 L/h	1 L/h	1.2 L/h	1.4 L/h	1.6 L/h
DIMENSIONI (LXPXH)			700 x 830 x 1700 (mm)				
CONNESIONE GAS				1/4" gas			
CONNESIONE RETE			Ethernet - Modbus TCP/IP				
PESO	300 Kg	305 Kg	310 Kg	340 Kg	345 Kg	350 Kg	355 Kg



DON'T BUY GAS **GENERATE IT!**



  Sirio generators are entirely designed and manufactured in Italy by:
I generatori Sirio sono interamente progettati e fabbricati in Italia da:



ErreDue spa
Via G. Gozzano, 3 – 57121 Livorno Italy
Tel. +39 0586 444066
Fax +39 0586 444212
Email: info@erreduegas.it

www.erreduegas.it



Distribuito da / Distributed by:

